

Montgomery County Public Schools Facilities Guide

DIVISION 10 – SPECIALTIES

SECTION 10010

MISCELLANEOUS SPECIALTIES

PART 1 GENERAL

1.01 GUIDE INCLUDES

- A. Broom and Mop Holders
- B. Fire Extinguishers
- C. Privacy Curtains
- D. Shower Receptors

1.02 SUBMITTALS

- A. Submit location of manufacture of miscellaneous specialties.
- B. Submit certification that fire extinguishers are halon-free.

PART 2 PRODUCTS

2.01 BROOM & MOP HOLDERS

- A. Provide one broom and mop rack at each building service closet.
- B. Materials:
 - 1. Holders: Cadmium plated steel ribbed with pivoted serrated rubber cam riveted to mounting strip.
 - 2. Mounting Strip: 3 inch channel of Type 320 (18-8) stainless steel with No.4 satin finish approximately 36 inches long and 4 holders.
- C. Manufacturers and Models:
 - 1. ASI, No. 8215
 - 2. McKinney/Parker Co., No. 608
 - 3. Bobrick Washroom Equipment, No. 223
- D. Use stainless steel or cadmium plated screws in expansion shields.

2.02 FIRE EXTINGUISHERS

- A. Furnished and installed by Owner at these locations only: Chemistry Labs, Home Economics Rooms, TV Studios, Wood Shops, Auto Shops, Body Shops, Kitchens, Boiler Rooms and Stages. Mounted 45 inches from floor free from obstructions. (Architect to provide adequate space and location for surfaced mounted units)
- B. No fire extinguisher cabinets or recesses in walls shall be provided.
- C. Fire extinguishers shall be certified HCFC- and halon-free.

2.03 PRIVACY CURTAINS

- A. Provide in health rooms and other locations as noted on the drawings.
- B. Materials:
 - 1. Type shall be cubical track surface mounted to the ceiling. Track shall be 1-3/8 inches X 3/4 inch aluminum alloy 6063-T5 extruded and anodized. Provide 12 inch radius for 90 degree bends.
 - 2. Carriers shall be nickel plated brass axle with nylon wheels and nickel plated steel ball chain and hook spaced at 6 inches.

3. Curtain to be 10 percent greater than track length and shall be 100 percent trevira polyester yarn with inherent permanent flame resistance. Fabric shall be 13.5 oz per linear yard and meet NFPA 701 for vertical flammability. Provide nylon mesh top and chrome plated brass grommets at 6 inches o.c.
- C. Manufacturers and Models:
1. AR Nelson Co., Model 1200
 2. General Cubical, Model 1062N
 3. Lanshire, Model 36-419
 4. Imperial Fastener Co., IFC-98 w/IFC-100

2.04 SHOWER RECEPTORS

- A. Location: Provide at each shower
- B. Size: 36 inch X 36 inch unless noted otherwise
- C. Type: Terrazzo by Florestone Products Co.

END OF SECTION