# MCPS Office of Facilities Management Division of Sustainability and Compliance Indoor Air Quality (IAQ)

#### **Poolesville High School IAQ Sensor Monitoring**

Reporting Period: February 05, 2024 – February 09, 2024

Report Date: February 13, 2024

#### MCPS personnel reviewed the following:

- Construction Activities as reported by the MCPS Division of Design and Construction (DDC) to the Poolesville High School (PHS) Administration for inclusion in the community update notification.
- IAQ sensor data included in the Poolesville HS On-Site Construction IAQ Report.

#### **Summary Observations:**

- No notifications or alerts were triggered during the reporting period.
- IAQ Sensor data were reviewed daily by IAQ and DDC personnel.
- Approximately six (6) classrooms consistently indicate TVOC concentrations higher than the
  other classrooms for limited durations. These concentrations rise and fall at the same time as
  rises and falls in other IAQ parameters monitored, most likely related to occupancy and not an
  on-site or construction source.
- PM data show higher concentrations for limited durations throughout the instructional day in approximately six (6) different classrooms. These concentrations rise and fall at the same time as rises and falls in other IAQ parameters monitored, most likely related to occupancy and not an on-site or construction source.

#### **Construction Activities:**

• Construction activity reported in the main gym on 2/9/24 resulted in odors in the school associated with line painting in the gym. The line painting was stopped and fans were placed in the gym to pull the odors out of the building. Review of the data collected does not indicate construction activities impacted indoor air quality at PHS.

#### Response Action(s):

• Both IAQ and DDC staff will continue to monitor sensor data at PHS.

#### Attachments:

 Poolesville HS On-Site Construction IAQ Reports for February 05, 2024 through February 09, 2024.

# POOLESVILLE HS ON-SITE CONSTRUCTION IAQ REPORT



This report was generated on 02/06/2024 at 07:55 AM (America/New\_York)

This daily report is for IAQ data collected between 6:00 AM and 6:00 PM for the day previous to the report generated date above.

This report includes the parameters that are most affected by construction activities in close proximity to an occupied buildings:

CO - carbon monoxide

TVOC - total volatile organic compounds

PM10 - particulate matter <=10 micron(ug)

PM2.5 - particulate matter <= 2.5 ug

PM1.0 - particulate matter <= 1.0 ug

ppm - parts per million

ppb - parts per billion

ug/m3 - micrograms per cubic meter of air

All data is monitored as an indicator of ventilation performance. Where suspect ventilation concerns are identified IAQ team members investigate to determine best next steps, including but not limited to - submit work orders to mechanical teams for repairs, review occupancy and use, review occupant activities and or continue to monitor data collected for patterns and trends.

### CO Monitoring

Carbon Monoxide (CO): Carbon monoxide is a colorless, odorless gas. It results from incomplete combustion processes. Common sources of CO in schools are improperly vented furnaces, malfunctioning gas ranges, canned heat (e.g. a Sterno), or exhaust fumes that have been drawn back into the building. Worn or poorly adjusted and maintained combustion devices (e.g., boilers, furnaces), or a flue that is improperly sized, blocked, disconnected, or leaking, can be significant sources. Auto, truck, or bus exhaust from attached garages, nearby roads, or idling vehicles in parking areas can also be sources. Carbon monoxide at high concentrations is considered to be a serious health hazard.


# CO Graphs Legend:


solid lines- indicate data from each room

dashed lines appear when data exceeds value for any period of time

IAQ - yellow = 4 ppm; MCPS notified at 4-hours

Ventilation - orange = 9 ppm; MCPS notified at 1-hour; immediate text, investigation Health & Safety - red = 25 ppm; MCPS notified at 8-hours, immediate text, community notification if during school hours







The carbon monoxide standards for indoor air quality are the U.S. Environmental Protection Agency (US EPA) National Ambient Air Quality Standard (NAAQS) of 9 ppm CO on a 8-hour time-weighted average (TWA), and the World Health organization Guidelines for Indoor Air Quality – Selected Pollutants of 6 ppm. However, MCPS will be notified at a sustained measurement of 4 ppm or greater for 4-hours as a more conservative and precautionary approach to this health-based standard.


#### TVOC Monitoring


TVOC Graphs Legend:


solid lines indicate data from each room dashed lines appear when exceeds value for any period of time IAQ - yellow = 500 ppb (0.5 ppm); MCPS notified at 4-hours Ventilation - red = 10,000 ppb (10 ppm); MCPS notified at 4-hours














### PM1.0 Monitoring


### PM1.0 Graphs Legend:

solid lines- indicate data from each room dashed lines appear when data exceeds value for any period of time IAQ - yellow = 8 ug/m3; MCPS notified at 4-hours Ventilation - orange = 150 ug/m3; MCPS notified at 2-hours Health & Safety - red = 250 ug/m3; MCPS notified at 8-hours










- 32

SCI-33

— 33В

— 33A




### PM2.5 Monitoring


PM2.5 Graphs Legend:


solid lines- indicate data from each room dashed lines appear when data exceeds value for any period of time IAQ - yellow = 12 ug/m3; MCPS notified at 4-hours Ventilation - orange = 150 ug/m3; MCPS notified at 2-hours Health & Safety - red = 250 ug/m3; MCPS notified at 8-hours


- SCI-26


— SCI-28













### PM10 Monitoring


PM10 Graphs Legend:

solid lines- indicate data from each room dashed lines appear when data exceeds value for any period of time IAQ - yellow = 50 ug/m3; MCPS notified at 4-hours Ventilation - orange = 355 ug/m3; MCPS notified at 2-hours Health & Safety - red = 425 ug/m3; MCPS notified at 8-hours

















12:00

13:00

14:00

— SCI-195 — SCI-293 — SCI-198

15:00

16:00

— SCI-205

17:00

06:00

07:00

08:00

09:00

— SCI-189 — SCI-285

10:00

11:00

— SCI-199

18:00

# POOLESVILLE HS ON-SITE CONSTRUCTION IAQ REPORT



This report was generated on 02/07/2024 at 07:38 AM (America/New\_York)

This daily report is for IAQ data collected between 6:00 AM and 6:00 PM for the day previous to the report generated date above.

This report includes the parameters that are most affected by construction activities in close proximity to an occupied buildings:

CO - carbon monoxide

TVOC - total volatile organic compounds

PM10 - particulate matter <=10 micron(ug)

PM2.5 - particulate matter <= 2.5 ug

PM1.0 - particulate matter <= 1.0 ug

ppm - parts per million

ppb - parts per billion

ug/m3 - micrograms per cubic meter of air

All data is monitored as an indicator of ventilation performance. Where suspect ventilation concerns are identified IAQ team members investigate to determine best next steps, including but not limited to - submit work orders to mechanical teams for repairs, review occupancy and use, review occupant activities and or continue to monitor data collected for patterns and trends.

### CO Monitoring

Carbon Monoxide (CO): Carbon monoxide is a colorless, odorless gas. It results from incomplete combustion processes. Common sources of CO in schools are improperly vented furnaces, malfunctioning gas ranges, canned heat (e.g. a Sterno), or exhaust fumes that have been drawn back into the building. Worn or poorly adjusted and maintained combustion devices (e.g., boilers, furnaces), or a flue that is improperly sized, blocked, disconnected, or leaking, can be significant sources. Auto, truck, or bus exhaust from attached garages, nearby roads, or idling vehicles in parking areas can also be sources. Carbon monoxide at high concentrations is considered to be a serious health hazard.


# CO Graphs Legend:


solid lines- indicate data from each room

dashed lines appear when data exceeds value for any period of time

IAQ - yellow = 4 ppm; MCPS notified at 4-hours

Ventilation - orange = 9 ppm; MCPS notified at 1-hour; immediate text, investigation Health & Safety - red = 25 ppm; MCPS notified at 8-hours, immediate text, community notification if during school hours






The carbon monoxide standards for indoor air quality are the U.S. Environmental Protection Agency (US EPA) National Ambient Air Quality Standard (NAAQS) of 9 ppm CO on a 8-hour time-weighted average (TWA), and the World Health organization Guidelines for Indoor Air Quality – Selected Pollutants of 6 ppm. However, MCPS will be notified at a sustained measurement of 4 ppm or greater for 4-hours as a more conservative and precautionary approach to this health-based standard.


#### TVOC Monitoring


### TVOC Graphs Legend:


solid lines indicate data from each room dashed lines appear when exceeds value for any period of time IAQ - yellow = 500 ppb (0.5 ppm); MCPS notified at 4-hours Ventilation - red = 10,000 ppb (10 ppm); MCPS notified at 4-hours


ppb




















### PM1.0 Monitoring


## PM1.0 Graphs Legend:


solid lines- indicate data from each room dashed lines appear when data exceeds value for any period of time IAQ - yellow = 8 ug/m3; MCPS notified at 4-hours Ventilation - orange = 150 ug/m3; MCPS notified at 2-hours Health & Safety - red = 250 ug/m3; MCPS notified at 8-hours













### PM2.5 Monitoring


PM2.5 Graphs Legend:


solid lines- indicate data from each room dashed lines appear when data exceeds value for any period of time IAQ - yellow = 12 ug/m3; MCPS notified at 4-hours Ventilation - orange = 150 ug/m3; MCPS notified at 2-hours Health & Safety - red = 250 ug/m3; MCPS notified at 8-hours











12:00

<del>---</del> 32

<del>---</del> 29

13:00

— SCI-33

14:00

— 33В


— 33A

16:00

<del>---</del> 35

17:00

18:00



### PM10 Monitoring

06:00

07:00

08:00

09:00


- SCI-26


10:00


— SCI-28


## PM10 Graphs Legend:


solid lines- indicate data from each room dashed lines appear when data exceeds value for any period of time IAQ - yellow = 50 ug/m3; MCPS notified at 4-hours Ventilation - orange = 355 ug/m3; MCPS notified at 2-hours Health & Safety - red = 425 ug/m3; MCPS notified at 8-hours











# POOLESVILLE HS ON-SITE CONSTRUCTION IAQ REPORT



This report was generated on 02/08/2024 at 12:53 PM (America/New\_York)

This daily report is for IAQ data collected between 6:00 AM and 6:00 PM for the day previous to the report generated date above.

This report includes the parameters that are most affected by construction activities in close proximity to an occupied buildings:

CO - carbon monoxide

TVOC - total volatile organic compounds

PM10 - particulate matter <=10 micron(ug)

PM2.5 - particulate matter <= 2.5 ug

PM1.0 - particulate matter <= 1.0 ug

ppm - parts per million

ppb - parts per billion

ug/m3 - micrograms per cubic meter of air

All data is monitored as an indicator of ventilation performance. Where suspect ventilation concerns are identified IAQ team members investigate to determine best next steps, including but not limited to - submit work orders to mechanical teams for repairs, review occupancy and use, review occupant activities and or continue to monitor data collected for patterns and trends.

#### CO Monitoring

Carbon Monoxide (CO): Carbon monoxide is a colorless, odorless gas. It results from incomplete combustion processes. Common sources of CO in schools are improperly vented furnaces, malfunctioning gas ranges, canned heat (e.g. a Sterno), or exhaust fumes that have been drawn back into the building. Worn or poorly adjusted and maintained combustion devices (e.g., boilers, furnaces), or a flue that is improperly sized, blocked, disconnected, or leaking, can be significant sources. Auto, truck, or bus exhaust from attached garages, nearby roads, or idling vehicles in parking areas can also be sources. Carbon monoxide at high concentrations is considered to be a serious health hazard.


## CO Graphs Legend:


solid lines- indicate data from each room

dashed lines appear when data exceeds value for any period of time

IAQ - yellow = 4 ppm; MCPS notified at 4-hours

Ventilation - orange = 9 ppm; MCPS notified at 1-hour; immediate text, investigation Health & Safety - red = 25 ppm; MCPS notified at 8-hours, immediate text, community notification if during school hours







The carbon monoxide standards for indoor air quality are the U.S. Environmental Protection Agency (US EPA) National Ambient Air Quality Standard (NAAQS) of 9 ppm CO on a 8-hour time-weighted average (TWA), and the World Health organization Guidelines for Indoor Air Quality – Selected Pollutants of 6 ppm. However, MCPS will be notified at a sustained measurement of 4 ppm or greater for 4-hours as a more conservative and precautionary approach to this health-based standard.


#### TVOC Monitoring

### TVOC Graphs Legend:

solid lines indicate data from each room dashed lines appear when exceeds value for any period of time IAQ - yellow = 500 ppb (0.5 ppm); MCPS notified at 4-hours Ventilation - red = 10,000 ppb (10 ppm); MCPS notified at 4-hours











ppb








### PM1.0 Monitoring

### PM1.0 Graphs Legend:

solid lines- indicate data from each room dashed lines appear when data exceeds value for any period of time IAQ - yellow = 8 ug/m3; MCPS notified at 4-hours Ventilation - orange = 150 ug/m3; MCPS notified at 2-hours Health & Safety - red = 250 ug/m3; MCPS notified at 8-hours











μg/m³






### PM2.5 Monitoring

PM2.5 Graphs Legend:


solid lines- indicate data from each room dashed lines appear when data exceeds value for any period of time IAQ - yellow = 12 ug/m3; MCPS notified at 4-hours Ventilation - orange = 150 ug/m3; MCPS notified at 2-hours Health & Safety - red = 250 ug/m3; MCPS notified at 8-hours





SCI-189


SCI-198

— SCI-210












### PM10 Monitoring


## PM10 Graphs Legend:


solid lines- indicate data from each room dashed lines appear when data exceeds value for any period of time IAQ - yellow = 50 ug/m3; MCPS notified at 4-hours Ventilation - orange = 355 ug/m3; MCPS notified at 2-hours Health & Safety - red = 425 ug/m3; MCPS notified at 8-hours











# POOLESVILLE HS ON-SITE CONSTRUCTION IAQ REPORT



This report was generated on 02/09/2024 at 03:00 AM (America/New\_York)

This daily report is for IAQ data collected between 6:00 AM and 6:00 PM for the day previous to the report generated date above.

This report includes the parameters that are most affected by construction activities in close proximity to an occupied buildings:

CO - carbon monoxide

TVOC - total volatile organic compounds

PM10 - particulate matter <=10 micron(ug)

PM2.5 - particulate matter <= 2.5 ug

PM1.0 - particulate matter <= 1.0 ug

ppm - parts per million

ppb - parts per billion

ug/m3 - micrograms per cubic meter of air

All data is monitored as an indicator of ventilation performance. Where suspect ventilation concerns are identified IAQ team members investigate to determine best next steps, including but not limited to - submit work orders to mechanical teams for repairs, review occupancy and use, review occupant activities and or continue to monitor data collected for patterns and trends.

### CO Monitoring

Carbon Monoxide (CO): Carbon monoxide is a colorless, odorless gas. It results from incomplete combustion processes. Common sources of CO in schools are improperly vented furnaces, malfunctioning gas ranges, canned heat (e.g. a Sterno), or exhaust fumes that have been drawn back into the building. Worn or poorly adjusted and maintained combustion devices (e.g., boilers, furnaces), or a flue that is improperly sized, blocked, disconnected, or leaking, can be significant sources. Auto, truck, or bus exhaust from attached garages, nearby roads, or idling vehicles in parking areas can also be sources. Carbon monoxide at high concentrations is considered to be a serious health hazard.


## CO Graphs Legend:


solid lines- indicate data from each room

dashed lines appear when data exceeds value for any period of time

IAQ - yellow = 4 ppm; MCPS notified at 4-hours

Ventilation - orange = 9 ppm; MCPS notified at 1-hour; immediate text, investigation Health & Safety - red = 25 ppm; MCPS notified at 8-hours, immediate text, community notification if during school hours







The carbon monoxide standards for indoor air quality are the U.S. Environmental Protection Agency (US EPA) National Ambient Air Quality Standard (NAAQS) of 9 ppm CO on a 8-hour time-weighted average (TWA), and the World Health organization Guidelines for Indoor Air Quality – Selected Pollutants of 6 ppm. However, MCPS will be notified at a sustained measurement of 4 ppm or greater for 4-hours as a more conservative and precautionary approach to this health-based standard.


#### TVOC Monitoring


### TVOC Graphs Legend:

solid lines indicate data from each room dashed lines appear when exceeds value for any period of time IAQ - yellow = 500 ppb (0.5 ppm); MCPS notified at 4-hours Ventilation - red = 10,000 ppb (10 ppm); MCPS notified at 4-hours











ppb 4000








### PM1.0 Monitoring


### PM1.0 Graphs Legend:


solid lines- indicate data from each room dashed lines appear when data exceeds value for any period of time IAQ - yellow = 8 ug/m3; MCPS notified at 4-hours Ventilation - orange = 150 ug/m3; MCPS notified at 2-hours Health & Safety - red = 250 ug/m3; MCPS notified at 8-hours














#### PM2.5 Monitoring


PM2.5 Graphs Legend:


solid lines- indicate data from each room dashed lines appear when data exceeds value for any period of time IAQ - yellow = 12 ug/m3; MCPS notified at 4-hours Ventilation - orange = 150 ug/m3; MCPS notified at 2-hours Health & Safety - red = 250 ug/m3; MCPS notified at 8-hours













#### PM10 Monitoring


PM10 Graphs Legend:


solid lines- indicate data from each room dashed lines appear when data exceeds value for any period of time IAQ - yellow = 50 ug/m3; MCPS notified at 4-hours Ventilation - orange = 355 ug/m3; MCPS notified at 2-hours Health & Safety - red = 425 ug/m3; MCPS notified at 8-hours














# POOLESVILLE HS ON-SITE CONSTRUCTION IAQ REPORT



This report was generated on 02/10/2024 at 03:00 AM (America/New\_York)

This daily report is for IAQ data collected between 6:00 AM and 6:00 PM for the day previous to the report generated date above.

This report includes the parameters that are most affected by construction activities in close proximity to an occupied buildings:

CO - carbon monoxide

TVOC - total volatile organic compounds

PM10 - particulate matter <=10 micron(ug)

PM2.5 - particulate matter <= 2.5 ug

PM1.0 - particulate matter <= 1.0 ug

ppm - parts per million

ppb - parts per billion

ug/m3 - micrograms per cubic meter of air

All data is monitored as an indicator of ventilation performance. Where suspect ventilation concerns are identified IAQ team members investigate to determine best next steps, including but not limited to - submit work orders to mechanical teams for repairs, review occupancy and use, review occupant activities and or continue to monitor data collected for patterns and trends.

#### CO Monitoring

Carbon Monoxide (CO): Carbon monoxide is a colorless, odorless gas. It results from incomplete combustion processes. Common sources of CO in schools are improperly vented furnaces, malfunctioning gas ranges, canned heat (e.g. a Sterno), or exhaust fumes that have been drawn back into the building. Worn or poorly adjusted and maintained combustion devices (e.g., boilers, furnaces), or a flue that is improperly sized, blocked, disconnected, or leaking, can be significant sources. Auto, truck, or bus exhaust from attached garages, nearby roads, or idling vehicles in parking areas can also be sources. Carbon monoxide at high concentrations is considered to be a serious health hazard.


# CO Graphs Legend:


solid lines- indicate data from each room

dashed lines appear when data exceeds value for any period of time

IAQ - yellow = 4 ppm; MCPS notified at 4-hours

Ventilation - orange = 9 ppm; MCPS notified at 1-hour; immediate text, investigation Health & Safety - red = 25 ppm; MCPS notified at 8-hours, immediate text, community notification if during school hours






The carbon monoxide standards for indoor air quality are the U.S. Environmental Protection Agency (US EPA) National Ambient Air Quality Standard (NAAQS) of 9 ppm CO on a 8-hour time-weighted average (TWA), and the World Health organization Guidelines for Indoor Air Quality – Selected Pollutants of 6 ppm. However, MCPS will be notified at a sustained measurement of 4 ppm or greater for 4-hours as a more conservative and precautionary approach to this health-based standard.

#### TVOC Monitoring

TVOC Graphs Legend:


solid lines indicate data from each room dashed lines appear when exceeds value for any period of time IAQ - yellow = 500 ppb (0.5 ppm); MCPS notified at 4-hours Ventilation - red = 10,000 ppb (10 ppm); MCPS notified at 4-hours










ppb 4000











#### PM1.0 Monitoring

#### PM1.0 Graphs Legend:


solid lines- indicate data from each room dashed lines appear when data exceeds value for any period of time IAQ - yellow = 8 ug/m3; MCPS notified at 4-hours Ventilation - orange = 150 ug/m3; MCPS notified at 2-hours Health & Safety - red = 250 ug/m3; MCPS notified at 8-hours









μg/m³ - 20 Main Building (Admin, BLR & CRs South) - Maximum Value Daily Trend - PM1.0 (ug/mg3)










#### PM2.5 Monitoring


## PM2.5 Graphs Legend:


solid lines- indicate data from each room dashed lines appear when data exceeds value for any period of time IAQ - yellow = 12 ug/m3; MCPS notified at 4-hours Ventilation - orange = 150 ug/m3; MCPS notified at 2-hours Health & Safety - red = 250 ug/m3; MCPS notified at 8-hours











#### PM10 Monitoring

## PM10 Graphs Legend:

solid lines- indicate data from each room dashed lines appear when data exceeds value for any period of time IAQ - yellow = 50 ug/m3; MCPS notified at 4-hours Ventilation - orange = 355 ug/m3; MCPS notified at 2-hours Health & Safety - red = 425 ug/m3; MCPS notified at 8-hours

